

Troll Standard 55

Controller with 55 mm external dimensions

Overview of advantages

- Simple end point setting with electronic RolloTube tubular motors:
Subsequent adjustment / modification of the end points is possible at any time.
- Automatic timer:
Programmable opening and closing times
- Display with contrast adjustment:
Simple menu-driven operation
- Auto / Manual switchover
- Automatic Summer / Winter changeover
- Extension input
- Available in ultra-white (-UW) and aluminium (-AL)



2620 (actual size)

The controller is designed in accordance with DIN 49075 (50 x 50 mm).

The controller can be used with all popular ranges of switches with the aid of an appropriate adapter frame.

- ① Controllers
- ② Adapter frame - switches product range (not included)
- ③ Frame - switches product range (not included)
- ④ Installation housing, suitable for fitting into a 58 mm flush-mounted box



Technical specifications

Item number	2620-UW / 2620-AL
Dimensions (LxW)	55 x 55 mm
Supply voltage	230 V / 50 Hz
Switching capacity	8 A (4 A)
Protection class	II
Standby consumption	2 w
Extension inputs	2 (230 V / 50 Hz)
Connection diameter	max. 1.5 mm ²
Permissible ambient temperature	0 to 40 °C
Power reserve	approx. 8 hrs
Fits the following tubular motors	RolloTube Basic, RolloTube Standard, RolloTube Comfort
Complies with the European Low Voltage Directive and EMC Directive	