



# RolloPort dta200

## Accessories



**4385**  
1-channel manual transmitter 433 MHz  
incl. bracket

---



**4385-4T**  
4-channel manual transmitter 433 MHz  
incl. bracket

---



**4360**  
2-channel micro manual transmitter 433 MHz

---



**4595**  
Key sensor with cylinder, flush-mounted,  
for opening the garage door manually from  
outside, lockable on both sides

---



**4596**  
Key sensor with cylinder, surface-mount-  
ed, for opening the garage door manually  
from outside, lockable on both sides

---



**4596-F**  
Radio key sensor with cylinder, surface-  
mounted, to operate the garage door drive  
by key, from outside, battery-operated

---



**4593**  
Key sensor without cylinder, flush-mount-  
ed (for profile cylinders with lockable set-  
ting 0° above, lockable on both sides)

---



**4594**  
Key sensor without cylinder, surface-mount-  
ed (for profile cylinders with lockable setting  
0° above, lockable on both sides)

---



**4594-F**  
Radio key sensor without cylinder, surface-  
mounted, to operate the garage door by key  
from outside, battery-operated

---



**4590**  
Internal sensor for opening the garage  
door

---



**4603**  
Standard code switch, code lock with number entry, consisting of a keypad and a control unit

---




**4603-F**  
Standard radio code switch, code lock with number entry

---



**4606-F**  
Comfort radio code switch, as 4603-F but with anti-vandal keypad

---



**4810**  
Connecting cable set, 7 m, junction box IP 54 and M16 x 1.5 mm screw fittings, for connecting the second drive to the control housing

---



**4811**  
Warning light 24 V, not auto-flashing, E14 lamp fitting, 25 w, with bulb

---



**4812**  
Electric lock 24 V, without profile cylinder, with side and ground locking plate for locking at the side or base

---



**4813**  
Rod aerial 434 / 433 MHz, external antenna, 50 Ohm co-axial cable

---



**4814**  
Non-reusable photo sensor, IP 44, surface-mounted, range 10 m, including fitting bracket, AC / DC 24 V

---



**4815**  
Wooden pole bracket, variable setting from 90 - 140 mm pole strength

---