

# Troll Basic 55

Controller with 55 mm external dimensions

## Overview of advantages

- Memory function:  
Simple repeat programmed timed function opening and closing times on a 24-hour cycle
- Local, manual operation with a sensor
- Auto / Manual switchover
- Extension input
- Group / Central control is possible
- Available in ultra-white (-UW) and aluminium (-AL)



2601 (actual size)

The controller is designed in accordance with DIN 49075 (50 x 50 mm).

The controller can be used with all popular ranges of switches with the aid of an appropriate adapter frame.

- ① Controllers
- ② Adapter ring frame - switches product range (not included)
- ③ Frame - switches product range (not included)
- ④ Installation housing, suitable for fitting into a 58 mm flush-mounted box



### Technical specifications

Item number	2601-UW / 2601-AL
Dimensions (LxW)	55 x 55 mm
Supply voltage	230 V / 50 Hz
Switching capacity	8 A (4 A)
Protection class	II
Standby consumption	< 1.4 w
Extension inputs	2 (230 V / 50 Hz)
Connection diameter	max. 1.5 mm <sup>2</sup>
Power reserve	approx. 10 min
Permissible ambient temperature	0 to 40 °C
Fits the following tubular motors	RolloTube Basic, RolloTube Standard, RolloTube Comfort
Complies with the European Low Voltage Directive and EMC Directive	